12 MAY 2005

## PCT

## NOTIFICATION CONCERNING THE FILING OF AMENDMENTS OF THE CLAIMS

(PCT Administrative Instructions, Section 417)

From the INTERNATIONAL BUREAU

WASHIDA, Kimihito 5th Floor, Shintoshicenter Bldg. 24-1, Tsurumaki 1-chome Tama-shi, Tokyo 206-0034 Japan

Date of mailing

(day/month/year) 22 July 2004 (22.07.2004)

Applicant's or agent's file reference

2F03177-PCT

International application No.

PCT/JP2003/014562

IMPORTANT NOTIFICATION

International filing date (day/month/year)

17 November 2003 (17.11.2003)

**Applicant** 

PANASONIC MOBILE COMMUNICATIONS CO., LTD. et al

1. The applicant is hereby notified that amendments to the claims under Article 19 were received by the International Bureau on:

15 July 2004 (15.07.2004)

2. This date is within the time limit under Rule 46.1.

Consequently, the international publication of the international application will contain the amended claims according to Rule 48.2(f), (h) and (i).

3. The applicant is reminded that the international application (description, claims and drawings) may be amended during the international preliminary examination under Chapter II, according to Article 34, and in any case, before each of the designated Offices, according to Article 28 and Rule 52, or before each of the elected Offices, according to Article 41

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Facsimile No. (41-22) 338.70.10

Authorised officer

Miki KOBAYASHI (Fax 338 7010)

6363671

Telephone No. (41-22) 338 9401

## JC20 Rec'd PCT/PTO 12 MAY 2005

1

What is claimed is:

- 1. (Cancelled)
- 2. (Cancelled)
- 5 3. (Cancelled)
  - 4. (Cancelled)
  - 5. (Cancelled)
- (Added) An active antenna having a multilayer structure
   comprising:

an antenna substrate on which an antenna is disposed;
a circuit substrate on which an amplification
circuit for a signal transmitted/received through said
antenna; and

a heat radiation plate interposed between said antenna substrate and said circuit substrate,

wherein said heat radiation plate includes a communication hole that communicates said antenna substrate side with said circuit substrate side.

20

2. (Added) The active antenna according to claim 1, wherein said antenna is disposed apart from said communication hole on said antenna substrate and is supplied power from said communication hole through a feed line.

25

3. (Added) The active antenna according to claim 2, wherein said communication hole is slot-shaped, and

said feed line is disposed in a direction

perpendicular to the longitudinal direction of the slot shape of said communication hole on said antenna substrate.

4. (Added) The active antenna according to claim 3, wherein said length in the longitudinal direction of said communication hole is determined based on both the thickness of said heat radiation plate and the frequency used of said antenna.

10

5. (Added) An active antenna comprising:

an antenna;

a high-output amplifier that amplifies a signal and outputs the signal to said antenna;

a low-noise amplifier that amplifies the signal received by said antenna;

an antenna substrate that includes said antenna and a feeder circuit that feeds power to said antenna;

an RF substrate that is mounted with said high-output

amplifier and said low-noise amplifier which are active

devices; and

a heat radiation block inserted between said antenna substrate and said RF substrate,

wherein said antenna substrate and said RF substrate

25 are connected through an electromagnetic field by a

connection slot.

6. (Added) The active antenna according to claim 5, further

comprising:

10

a plurality of said antennas;

the same number of said high-output amplifiers as said antennas;

a splitter that splits a signal into as many signals as said antennas and outputs the signals to said high-output amplifier; and

a combiner that combines the signals received by said antennas and outputs the combined signal to said low-noise amplifier,

wherein signals are spatially combined.

- 7. (Added) The active antenna according to claim 6, wherein a variable phase circuit is interposed between said
  15 high-output amplifier and said splitter or between said high-output amplifier and said antenna.
- 8. (Added) The active antenna according to claim 6, wherein a variable gain circuit is interposed between said
  20 high-output amplifier and said splitter or between said high-output amplifier and said antenna.
- 9. (Added) The active antenna according to claim 6, wherein a variable phase circuit is interposed between said combiner and said antenna.
  - 10. (Added) An active antenna manufacturing method comprising:

a step of providing a slot-shaped through hole in a heat radiation plate; and

a step of forming a multilayer structure comprising an antenna substrate on which an antenna is disposed, a circuit substrate on which an amplification circuit for a signal transmitted/received through said antenna and a heat radiation plate provided with a through hole interposed between said antenna substrate and said circuit substrate.

5